

SDS: 0062453 **Version**: 1 **Date Prepared**: 12/28/2021 Page 1 of 2

NEW ZEALAND SUPPLEMENT

Product Name: CUROX M-200

DISTRIBUTOR/IMPORTER:

HS Composites

63 Hunua Road, Red Hill, Papakura 2110

For Product and all Non-Emergency Information call +64 (09) 295 2200 (business hours only) or contact us at http://www.allnex.com/contact

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

Poison Centre 0800 764 766

EPA New Zealand HSNO approval code or group standard: HSR002630

Group Standard: Organic Peroxides (Corrosive) Group Standard 2020

Signal Word DANGER

Flammable liquid hazard category: Category 4

Physical Hazard Statements

Combustible liquid Heating may cause a fire

CONTROL PARAMETERS - Limits

Dimethyl phthalate 131-11-3

New Zealand: 5 mg/m₃ (TWA)
ACGIH (TLV): 5 mg/m₃ (TWA)

Methyl ethyl ketone peroxides (MEKP) 1338-23-4
New Zealand: 0.2 ppm (Ceiling)
1.5 mg/m₃ (Ceiling)

ACGIH (TLV): 0.2 ppm (Ceiling)

2-Butanone (Methyl ethyl ketone) 78-93-3

New Zealand: 150 ppm (TWA)

445 mg/m₃ (TWA) 300 ppm (STEL) 890 mg/m₃ (STEL)

ACGIH (TLV): 300 ppm (STEL)

200 ppm (TWA)

Hydrogen peroxide 7722-84-1

CUROX M-200 SDS: 0062453 Print Date: 12/28/2021 Page 2 of 2

New Zealand: 1 ppm (TWA)

1.4 mg/m₃ (TWA)

ACGIH (TLV): 1 ppm (TWA)

Biological Exposure Limit(s)

2-Butanone (Methyl ethyl ketone) 78-93-3

Biological Exposure Indices 2 mg/L (urine - end of shift)

This supplement must be read in conjunction with the attached SDS.

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : CUROX M-200

Manufacturer or supplier's details

Company : United Initiators Pty Ltd

Address : 20-22 McPherson Street

Banksmeadow NSW 2019 Australia

Telephone : +61 2 9316 0035 (Monday–Friday office hours only)

Emergency telephone number: +49 89 744220 (24 hours specialist advise)

E-mail address : cs-initiators.au@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 1B

Serious eye damage/eye irri-

tation

: Category 1

Acute aquatic toxicity : Category 2

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H227 Combustible liquid.

H242 Heating may cause a fire.

H302 + H332 Harmful if swallowed or if inhaled H314 Causes severe skin burns and eye damage.

CUROX M-200



Version **Revision Date:** SDS Number: **Print Date:** 02.10.2017 60000000394 15.06.2018 1.1

H401 Toxic to aquatic life.

Precautionary statements

: Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.

P234 Keep only in original container.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Imme-diately call a POISON CENTER or doctor/ physician. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

Storage:

P405 Store locked up.

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding < 30

°C/ < 86 °F. Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 600000000394
 15.06.2018

Chemical nature : Organic Peroxide

Liquid mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|----------------------|-----------|-----------------------|
| dimethyl phthalate | 131-11-3 | >= 50 -<55 |
| 2-Butanone, peroxide | 1338-23-4 | >= 35 -<40 |
| Butanone | 78-93-3 | >=1 -<5 |
| Hydrogen peroxide | 7722-84-1 | >=1 -<5 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

Call a physician immediately.

If inhaled : Call a physician or poison control centre immediately.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Call a physician immediately.

If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes.

If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.
Call a physician immediately.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: Harmful if swallowed or if inhaled Causes serious eye damage.

Causes severe burns.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

CUROX M-200



Version **Revision Date:** SDS Number: **Print Date:** 02.10.2017 60000000394 15.06.2018 1.1

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire-:

fighting

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which

may auto-ignite.

The product burns violently.

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local cir-cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

Use water spray to cool unopened containers.

Special protective equipment:

nec-

for firefighters

Wear self-contained breathing apparatus for firefighting if

essary.

Use personal protective equipment.

Hazchem Code : 2WE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-:

tive equipment and emergency procedures

Remove all sources of ignition.

Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Use personal protective equipment.

Never return spills in original containers for re-use. Treat recovered material as described in the section

"Disposal considerations".





Version **Revision Date: SDS Number: Print Date:** 02.10.2017 60000000394 15.06.2018 1.1

Environmental precautions: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

containment and cleaning up

Methods and materials for : Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

fire and explosion

Advice on protection against: Keep away from heat and sources of ignition. Use only explo-

sion-proof equipment. Keep away from combustible material.

Advice on safe handling : Do not swallow.

> Do not breathe vapours/dust. Avoid contact with skin and eves. Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling. For personal protection see section 8.

Protect from contamination.

Hygiene measures : Keep away from food and drink.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the

product.

Conditions for safe storage: Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Electrical installations / working materials must comply with





 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Store in original container.

Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem-: <30°C

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------|-----------|-------------------------------------|--|--------|
| dimethyl phthalate | 131-11-3 | TWA | 5 mg/m3 | AU OEL |
| | | TWA | 5 mg/m3 | ACGIH |
| 2-Butanone, peroxide | 1338-23-4 | Peak limit | 0.2 ppm 1.5 mg/m3 | AU OEL |
| | | С | 0.2 ppm | ACGIH |
| Butanone | 78-93-3 | STEL | 300 ppm 890 mg/m3 | AU OEL |
| | | TWA | 150 ppm 445 mg/m3 | AU OEL |
| | | TWA | 200 ppm | ACGIH |
| | | STEL | 300 ppm | ACGIH |
| Hydrogen peroxide | 7722-84-1 | TWA | 1 ppm 1.4 mg/m3 | AU OEL |
| | | TWA | 1 ppm | ACGIH |

Biological occupational exposure limits

| Components | CAS-No. | Control | Biological | Sam- | Permissible | Basis |
|------------|---------|--------------|------------|-----------|-------------|-------|
| | | parameters | specimen | pling | concentra- | |
| | | | | time | tion | |
| Butanone | 78-93-3 | methyl ethyl | Urine | End of | 2 mg/l | ACGIH |
| | | ketone | | shift (As | | BEI |
| | | | | soon as | | |
| | | | | possible | | |
| | | | | after | | |
| | | | | exposure | | |
| | | | | ceases) | | |

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.





 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

Filter type : ABEK-filter

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless, red

Odour : characteristic

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : ca. 68 °C

Method: ISO 3679

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 500 hPa (55 °C)

Density : ca. 1.15 g/cm3 (20 °C)

Solubility(ies)

CUROX M-200



Version **Revision Date: SDS Number: Print Date:** 02.10.2017 60000000394 15.06.2018 1.1

Water solubility

slightly soluble

Solubility in other solvents: **Solvent: Phthalates**

Description: completely miscible

Partition coefficient: n-

octanol/water

: No data available

Self-Accelerating decomposi-: 60 °C

tion temperature (SADT)

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

: Stable under recommended storage conditions. Chemical stability

Possibility of hazardous reac-: Vapours may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

: Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled

Product:

Acute oral toxicity : Acute toxicity estimate: 1,224 mg/kg

Method: Calculation method

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

Acute inhalation toxicity : Acute toxicity estimate: 3.59 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

dimethyl phthalate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : (Rat): > 10.4 mg/l

Exposure time: 6 h

Test atmosphere: vapour

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Expert judgement

Acute inhalation toxicity Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg

Method: Expert judgement

Butanone:

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg

Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 6,500 mg/kg

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 600000000394
 15.06.2018

Skin corrosion/irritation Causes severe burns.

Product:

Remarks: Extremely corrosive and destructive to tissue.

Components:

dimethyl phthalate: Species: Rabbit Method: Draize Test Result: No skin irritation

2-Butanone, peroxide: Species: Rabbit Result: Causes burns.

Butanone:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Hydrogen peroxide:

Result: Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

dimethyl phthalate: Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

2-Butanone, peroxide:

Result: Irreversible effects on the eye

Butanone: Species: Rabbit Result: Eye irritation

Method: OECD Test Guideline 405

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

Hydrogen peroxide:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

dimethyl phthalate: Species: Mouse

Method: OECD Test Guideline 429

Result: Does not cause skin sensitisation.

2-Butanone, peroxide:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Assessment: Harmful if swallowed., Harmful if inhaled.

Butanone:

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

: Method: OECD Test Guideline 473

Result: negative

: Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat

Application Route: Intraperitoneal

Result: negative

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 600000000394
 15.06.2018

Test Type: Micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

2-Butanone, peroxide:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

: Method: OECD Test Guideline 471

Result: negative

: Method: OECD Test Guideline 476

Result: negative

Butanone:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

: Method: OECD Test Guideline 476

Result: negative

: Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Intraperitoneal Method: OECD Test Guideline 474

Result: negative

Hydrogen peroxide:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 451

Result: negative

Remarks: Based on data from similar materials

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

2-Butanone, peroxide:

Remarks: This information is not available.

Reproductive toxicity

Not classified based on available information.

Components:

dimethyl phthalate:

Effects on fertility : Species: Rat

Application Route: oral (gavage) Method: OECD Test Guideline 440

Result: negative

Effects on foetal develop-

ment

: Species: Rat

Application Route: Ingestion

General Toxicity Maternal: NOAEL: 840 mg/kg body weight Developmental Toxicity: NOAEL: 3,570 mg/kg body weight

Method: OECD Test Guideline 414

2-Butanone, peroxide:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity - Parent: NOAEL: 50 mg/kg body weight

Method: OECD Test Guideline 421

Result: negative

Butanone:

Effects on fertility : Species: Rat

Application Route: oral (drinking water)
General Toxicity - Parent: NOAEL: 10,000 mg/l
General Toxicity F1: NOAEL: 10,000 mg/l

Method: OECD Test Guideline 416

Remarks: Based on data from similar materials

Species: Rat

Application Route: oral (drinking water)
General Toxicity - Parent: LOAEL: 20,000 mg/l

Method: OECD Test Guideline 416

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

: Species: Rat

Application Route: Inhalation

General Toxicity Maternal: NOAEC: ca. 1,002 mg/kg body

weiaht

Teratogenicity: NOAEC Parent: ca. 1,002 mg/kg body weight

Method: OECD Test Guideline 414

Result: negative

STOT - single exposure

Not classified based on available information.

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

Components:

Hydrogen peroxide:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

dimethyl phthalate:

Species: Rat NOAEL: 770 mg/kg Application Route: Oral Exposure time: 16 w

Method: OECD Test Guideline 408

2-Butanone, peroxide:

Species: Rat

NOAEL: 200 mg/kg

Application Route: oral (gavage)

Exposure time: 28 d

Method: OECD Test Guideline 407

Repeated dose toxicity - : Harmful if swallowed., Harmful if inhaled.

Assessment

Hydrogen peroxide:

Species: Mouse

Application Route: Ingestion

Exposure time: 90 d

Symptoms: No adverse effects

Aspiration toxicity

Not classified based on available information.

Components:

dimethyl phthalate:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

dimethyl phthalate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 52 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

tox-icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 11 mg/l

Exposure time: 102 d

Method: OECD Test Guideline 210

LOEC (Oncorhynchus mykiss (rainbow trout)): 24 mg/l

Exposure time: 102 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 21 d

LOEC (Daphnia magna (Water flea)): 23 mg/l

Exposure time: 21 d

Toxicity to microorganisms : EC50: 4,100 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

2-Butanone, peroxide:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 44.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

NOEC (Poecilia reticulata (guppy)): 18 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 39 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6

mg/l

Exposure time: 72 h

CUROX M-200



Version **Revision Date: SDS Number: Print Date:** 02.10.2017 60000000394 15.06.2018 1.1

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms: EC50 (Bacteria): 48 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other: EC50 (Daphnia magna (Water flea)): 308 mg/l

aquatic invertebrates Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to microorganisms: NOEC (Pseudomonas putida): 1,150 mg/l

Exposure time: 16 h Method: DIN 38 412 Part 8

Hydrogen peroxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l

Exposure time: 96 h

Toxicity to daphnia and other: LC50 (Daphnia pulex (Water flea)): 2.4 mg/l

aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l

Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l

Exposure time: 72 h

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other: NOEC (Daphnia magna (Water flea)): 0.63 mg/l

Exposure time: 21 d

Toxicity to microorganisms: EC50: Method: OECD Test Guideline 209

Persistence and degradability

Components:

dimethyl phthalate:

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301E

2-Butanone, peroxide:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Butanone:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Hydrogen peroxide:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57

Method: OECD Test Guideline 305

Partition coefficient:

n-octanol/water

: log Pow: 1.54

2-Butanone, peroxide:

Partition coefficient:

n-octanol/water

: $\log Pow: < 0.3 (25 °C)$

Butanone:

Partition coefficient:

n-octanol/water

: log Pow: 0.3 (40 °C)

Hydrogen peroxide:

Partition coefficient: log Pow: -1.57

n-octanol/water Remarks: Calculation

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological

infor-mation

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal.

Toxic to aquatic life.

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

IATA-DGR

UN/ID No. : UN 3105

Proper shipping name : Organic peroxide type D, liquid

(Methyl ethyl ketone peroxide(s))

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen-: 570

ger aircraft)

IMDG-Code

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code Not applicable for product as supplied.

National Regulations

ADG

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 60000000394
 15.06.2018

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

(METHYL ETHYL KETONE PEROXIDE(S))

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 Hazchem Code : 2WE

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or

mix-ture

Standard for the Uniform

Scheduling of Medicines and

Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition or

notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory

legislation.

The components of this product are reported in the following inventories:

Schedule 6

AICS (AU) : On the inventory, or in compliance with the inventory

NZIoC (NZ) : On the inventory, or in compliance with the inventory

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : On TSCA Inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% re-sponse; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - Internation-

CUROX M-200



 Version
 Revision Date:
 SDS Number:
 Print Date:

 1.1
 02.10.2017
 600000000394
 15.06.2018

al Agency for Research on Cancer; IATA - International Air Transport Association; IBC - Interna-tional Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dan-gerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemi-cals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-vention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Tox-icology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Eco-nomic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Preven-tion; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -(Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concern-ing the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI -Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Con-trol Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date format : dd.mm.yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU/EN