

# SAFETY DATA SHEET



Crystic Primecoat

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Crystic Primecoat  
**Product code** : C1002400  
**Product type** : Liquid.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses        |
|------------------------|
| Intermediate compound. |

### 1.3 Details of the supplier of the safety data sheet

Scott Bader Co Ltd,  
Wollaston.  
Northants  
NN297RL  
United Kingdom  
+44 (0)1933663100

**e-mail address of person responsible for this SDS** : SDS@scottbader.com

### 1.4 Emergency telephone number

**Telephone number (Hours of operation)** : +44 1865 407333 (NCEC) 24h

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Acute Tox. 4, H332  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Carc. 2, H351  
Repr. 2, H361d (Unborn child)  
STOT SE 3, H335  
STOT RE 1, H372  
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

**Physical/chemical hazards** : Highly flammable.

**Human health hazards** : Possible risk of harm to the unborn child. Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Irritating to eyes and skin.

**Environmental hazards** : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the H statements declared above.

## SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

H225 - Highly flammable liquid and vapour.  
 H332 - Harmful if inhaled.  
 H319 - Causes serious eye irritation.  
 H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H361d - Suspected of damaging the unborn child.  
 H351 - Suspected of causing cancer.  
 H335 - May cause respiratory irritation.  
 H372 - Causes damage to organs through prolonged or repeated exposure.  
 H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention** :

P201 - Obtain special instructions before use.  
 P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P273 - Avoid release to the environment.  
 P260 - Do not breathe vapour.

**Response** :

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

**Storage** :

P405 - Store locked up.

**Disposal** :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** :

styrene  
 titanium dioxide  
 cobalt bis(2-ethylhexanoate)

**Supplemental label elements** :

Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification** :

None known.

### SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

| Product/ingredient name             | Identifiers  | %            | Classification  |         |
|-------------------------------------|--|--------------|---|---------|
|                                     |  |              | Regulation (EC) No. 1272/2008 [CLP]   | Type    |
| styrene                             | REACH #:<br>01-2119457861-32<br>EC: 202-851-5<br>CAS: 100-42-5<br>Index: 601-026-00-0  | ≥25 -<br>≤35 | Flam. Liq. 3, H226<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Repr. 2, H361d (Unborn child)<br>STOT SE 3, H335<br>STOT RE 1, H372 (hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | [1] [2] |
| butanone                            | REACH #:<br>01-2119457290-43<br>EC: 201-159-0<br>CAS: 78-93-3<br>Index: 606-002-00-3   | ≤5           | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066   | [1] [2] |
| titanium dioxide                    | REACH #:<br>01-2119489379-17<br>EC: 236-675-5<br>CAS: 13463-67-7                       | ≤3           | Carc. 2, H351 (inhalation)  | [1] [2] |
| cobalt bis<br>(2-ethylhexanoate)    | REACH #:<br>01-2119524678-29<br>EC: 205-250-6<br>CAS: 136-52-7                         | <1           | Eye Irrit. 2, H319<br>Skin Sens. 1A, H317<br>Repr. 2, H361f (Fertility)<br>Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 3, H412   | [1] [2] |
| xylene                              | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | ≤0.3         | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373 (inhalation)<br>Asp. Tox. 1, H304   | [1] [2] |
| ethanediol                          | EC: 203-473-3<br>CAS: 107-21-1<br>Index: 603-027-00-1                                  | ≤0.1         | Acute Tox. 4, H302<br>STOT RE 2, H373 (kidneys) (oral)  | [1] [2] |
| ethylbenzene                        | REACH #:<br>01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4  | ≤0.1         | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373 (hearing organs)<br>Asp. Tox. 1, H304   | [1] [2] |
| (2-methoxymethylethoxy)<br>propanol | EC: 252-104-2<br>CAS: 34590-94-8   | ≤0.1         | Not classified.   | [2]     |
| 2-methoxy-<br>1-methylethyl acetate | REACH #:<br>01-2119475791-29<br>EC: 203-603-9<br>CAS: 108-65-6<br>Index: 607-195-00-7  | ≤0.1         | Flam. Liq. 3, H226  | [2]     |
| 1-methoxy-2-propanol                | REACH #:<br>01-2119457435-35<br>EC: 203-539-1<br>CAS: 107-98-2<br>Index: 603-064-00-3  | ≤0.1         | Flam. Liq. 3, H226<br>STOT SE 3, H336   | [1] [2] |
| phenol                              | EC: 203-632-7<br>CAS: 108-95-2<br>Index: 604-001-00-2                                  | <0.1         | Acute Tox. 3, H301<br>Acute Tox. 3, H311<br>Acute Tox. 3, H331<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Muta. 2, H341  | [1] [2] |

Crystic Primecoat

### SECTION 3: Composition/information on ingredients

STOT RE 2, H373  
**See Section 16 for the full text of the H statements declared above.**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** :  Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** :  No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** :  Harmful if inhaled. May cause respiratory irritation.
- Skin contact** :  Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

## SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness
- Inhalation** : Adverse symptoms may include the following:  
 respiratory tract irritation  
 coughing  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide  
 metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Seveso Directive - Reporting thresholds (in tonnes)

##### Danger criteria

| Category  | Notification and MAPP threshold | Safety report threshold |
|---|---------------------------------|-------------------------|
| P5c: Flammable liquids 2 and 3 not falling under P5a or P5b | 5000                            | 50000                   |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name      | Exposure limit values   |
|------------------------------|---|
| styrene                      | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 250 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.<br>TWA: 430 mg/m <sup>3</sup> 8 hours.<br>STEL: 1080 mg/m <sup>3</sup> 15 minutes.  |
| butanone                     | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 899 mg/m <sup>3</sup> 15 minutes.<br>STEL: 300 ppm 15 minutes.<br>TWA: 600 mg/m <sup>3</sup> 8 hours.<br>TWA: 200 ppm 8 hours.  |
| titanium dioxide             | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: inhalable dust<br>TWA: 4 mg/m <sup>3</sup> 8 hours. Form: respirable dust   |
| cobalt bis(2-ethylhexanoate) | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Inhalation sensitiser.</b><br>TWA: 0.1 mg/m <sup>3</sup> , (as Co) 8 hours.   |
| xylene                       | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 441 mg/m <sup>3</sup> 15 minutes.<br>TWA: 50 ppm 8 hours.<br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>STEL: 100 ppm 15 minutes.   |
| ethanediol                   | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Particulate<br>STEL: 104 mg/m <sup>3</sup> 15 minutes. Form: Vapour<br>TWA: 52 mg/m <sup>3</sup> 8 hours. Form: Vapour<br>STEL: 40 ppm 15 minutes. Form: Vapour<br>TWA: 20 ppm 8 hours. Form: Vapour |

**SECTION 8: Exposure controls/personal protection**

|                                 |  |
|---------------------------------|--|
| ethylbenzene                    | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 552 mg/m <sup>3</sup> 15 minutes.<br>STEL: 125 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.<br>TWA: 441 mg/m <sup>3</sup> 8 hours. |
| (2-methoxymethylethoxy)propanol | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>TWA: 308 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.  |
| 2-methoxy-1-methylethyl acetate | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 548 mg/m <sup>3</sup> 15 minutes.<br>TWA: 50 ppm 8 hours.<br>TWA: 274 mg/m <sup>3</sup> 8 hours.<br>STEL: 100 ppm 15 minutes.  |
| 1-methoxy-2-propanol            | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 560 mg/m <sup>3</sup> 15 minutes.<br>STEL: 150 ppm 15 minutes.<br>TWA: 375 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours. |
| phenol                          | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>TWA: 2 ppm 8 hours.<br>STEL: 16 mg/m <sup>3</sup> 15 minutes.<br>STEL: 4 ppm 15 minutes.<br>TWA: 7.8 mg/m <sup>3</sup> 8 hours.      |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name | Type | Exposure              | Value                    | Population | Effects  |
|-------------------------|------|-----------------------|--------------------------|------------|----------|
| styrene                 | DNEL | Short term Inhalation | 289 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Short term Inhalation | 306 mg/m <sup>3</sup>    | Workers    | Local    |
|                         | DNEL | Long term Dermal      | 406 mg/kg bw/day         | Workers    | Systemic |
|                         | DNEL | Long term Inhalation  | 85 mg/m <sup>3</sup>     | Workers    | Systemic |
|                         | DNEL | Short term Inhalation | 174.25 mg/m <sup>3</sup> | Consumers  | Systemic |
|                         | DNEL | Short term Inhalation | 182.75 mg/m <sup>3</sup> | Consumers  | Local    |
|                         | DNEL | Long term Dermal      | 343 mg/kg bw/day         | Consumers  | Systemic |
|                         | DNEL | Long term Inhalation  | 10.2 mg/m <sup>3</sup>   | Consumers  | Systemic |
|                         | DNEL | Long term Oral        | 2.1 mg/kg                | Consumers  | Systemic |



**SECTION 8: Exposure controls/personal protection**

|                  |      |                          |                                 |                              |       |
|------------------|------|--------------------------|---------------------------------|------------------------------|-------|
| butanone         | DNEL | Long term Dermal         | bw/day<br>1161 mg/<br>kg bw/day | Workers                      | -     |
|                  | DNEL | Long term<br>Inhalation  | 600 mg/m <sup>3</sup>           | Workers                      | -     |
|                  | DNEL | Long term Dermal         | 412 mg/kg<br>bw/day             | Consumers                    | -     |
|                  | DNEL | Long term<br>Inhalation  | 106 mg/m <sup>3</sup>           | Consumers                    | -     |
|                  | DNEL | Long term Oral           | 31 mg/kg<br>bw/day              | Consumers                    | -     |
| titanium dioxide | DNEL | Long term<br>Inhalation  | 10 mg/m <sup>3</sup>            | Workers                      | Local |
| xylene           | DNEL | Short term<br>Inhalation | 442 mg/m <sup>3</sup>           | Workers                      | -     |
|                  | DNEL | Short term<br>Inhalation | 289 mg/m <sup>3</sup>           | Workers                      | -     |
|                  | DNEL | Long term<br>Inhalation  | 77 mg/m <sup>3</sup>            | Workers                      | -     |
|                  | DNEL | Long term<br>Inhalation  | 221 mg/m <sup>3</sup>           | Workers                      | -     |
|                  | DNEL | Long term Dermal         | 3182 mg/<br>kg bw/day           | Workers                      | -     |
|                  | DNEL | Long term Dermal         | 180 mg/kg<br>bw/day             | Workers                      | -     |
|                  | DNEL | Short term<br>Inhalation | 260 mg/m <sup>3</sup>           | Human via the<br>environment | -     |
|                  | DNEL | Long term<br>Inhalation  | 65.3 mg/m <sup>3</sup>          | Human via the<br>environment | -     |
|                  | DNEL | Dermal                   | 1872 mg/<br>kg bw/day           | Human via the<br>environment | -     |
|                  | DNEL | Long term Oral           | 12.5 mg/<br>kg bw/day           | Human via the<br>environment | -     |

**PNECs**

| Product/ingredient name   | Compartment Detail        | Value            | Method Detail |
|---------------------------|---------------------------|------------------|---------------|
| styrene                   | Fresh water               | 0.028 mg/l       | -             |
|                           | Marine water              | 0.0028 mg/l      | -             |
|                           | Fresh water sediment      | 0.614 mg/kg dwt  | -             |
|                           | Marine water sediment     | 0.0614 mg/kg dwt | -             |
|                           | Soil                      | 0.2 mg/kg dwt    | -             |
|                           | Sewage Treatment<br>Plant | 5 mg/l           | -             |
|                           | butanone                  | Fresh water      | 55.8 mg/l     |
| Marine water              |                           | 55.8 mg/l        | -             |
| Sewage Treatment<br>Plant |                           | 709 mg/l         | -             |
| Sediment                  |                           | 284.7 mg/kg      | -             |
| Soil                      |                           | 22.5 mg/kg       | -             |
| titanium dioxide          | Fresh water               | 0.127 mg/l       | -             |
|                           | Marine water              | ≥1 mg/l          | -             |
|                           | Fresh water sediment      | ≥1000 mg/l       | -             |
|                           | Marine water sediment     | ≥100 mg/l        | -             |
|                           | Soil                      | 100 mg/l         | -             |
|                           | Sewage Treatment<br>Plant | ≥100 mg/l        | -             |
| xylene                    | Fresh water               | 0.327 mg/l       | -             |
|                           | Marine water              | 0.327 mg/l       | -             |
|                           | Fresh water sediment      | 12.46 mg/kg      | -             |
|                           | Marine water sediment     | 12.46 mg/kg      | -             |
|                           | Soil                      | 2.31 mg/kg       | -             |
|                           | Sewage Treatment<br>Plant | 6.58 mg/l        | -             |

## SECTION 8: Exposure controls/personal protection

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.  
**Colour** : Not available.  
**Odour** : Solvent  
**Odour threshold** : Not available.  
**pH** : Not available.  
**Melting point/freezing point** : Not available.

## SECTION 9: Physical and chemical properties

|   |   |
|---|---|
| <b>Initial boiling point and boiling range</b>      | : Not available.                            |
| <b>Flash point</b>                                  | : Closed cup: 20°C                          |
| <b>Evaporation rate</b>                             | : Not available.                            |
| <b>Flammability (solid, gas)</b>                    | : Not available.                            |
| <b>Burning time</b>                                 | : Not applicable.                           |
| <b>Burning rate</b>                                 | : Not applicable.                           |
| <b>Upper/lower flammability or explosive limits</b> | : Not available.                            |
| <b>Vapour pressure</b>                              | : Not available.                            |
| <b>Vapour density</b>                               | : Not available.                            |
| <b>Relative density</b>                             | : 1.1 to 1.2                                |
| <b>Solubility(ies)</b>                              | : Not available.                            |
| <b>Solubility in water</b>                          | : Not available.                            |
| <b>Partition coefficient: n-octanol/ water</b>      | : Not available.                            |
| <b>Auto-ignition temperature</b>                    | : Not available.                            |
| <b>Decomposition temperature</b>                    | : Not available.                            |
| <b>Viscosity</b>                                    | : Kinematic (40°C): >0.4 cm <sup>2</sup> /s |
| <b>Explosive properties</b>                         | : Not available.                            |
| <b>Oxidising properties</b>                         | : Not available.                            |

### 9.2 Other information

|  |                   |
|--|-------------------|
| <b>Heat of combustion</b>                        | : Not available.  |
| <b>Enclosed space ignition - Time equivalent</b> | : Not applicable. |

No additional information.

## SECTION 10: Stability and reactivity

|  |   |
|--|---|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.  |
| <b>10.2 Chemical stability</b>                 | : The product is stable.  |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| <b>10.4 Conditions to avoid</b>                | : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |
| <b>10.5 Incompatible materials</b>             | : Reactive or incompatible with the following materials:<br>oxidizing materials   |
| <b>10.6 Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name         | Result                          | Species | Dose                    | Exposure |
|---------------------------------|---------------------------------|---------|-------------------------|----------|
| styrene                         | LC50 Inhalation Gas.            | Rat     | 2770 ppm                | 4 hours  |
|                                 | LC50 Inhalation Vapour          | Rat     | 11800 mg/m <sup>3</sup> | 4 hours  |
|                                 | LD50 Dermal                     | Rat     | >2000 mg/kg             | -        |
| butanone                        | LD50 Oral                       | Rat     | 2650 mg/kg              | -        |
|                                 | LD50 Dermal                     | Rabbit  | 6480 mg/kg              | -        |
| titanium dioxide                | LD50 Oral                       | Rat     | 2737 mg/kg              | -        |
|                                 | LC50 Inhalation Dusts and mists | Rat     | >6.8 mg/l               | 4 hours  |
| cobalt bis(2-ethylhexanoate)    | LD50 Oral                       | Rat     | >5000 mg/kg             | -        |
|                                 | LD50 Dermal                     | Rabbit  | >5 g/kg                 | -        |
| xylene                          | LD50 Oral                       | Rat     | >2000 mg/kg             | -        |
|                                 | LD50 Oral                       | Rat     | 4300 mg/kg              | -        |
| ethanediol                      | LD50 Oral                       | Rat     | 4700 mg/kg              | -        |
|                                 | LD50 Dermal                     | Rabbit  | >5000 mg/kg             | -        |
| ethylbenzene                    | LD50 Oral                       | Rat     | 3500 mg/kg              | -        |
|                                 | LD50 Dermal                     | Rabbit  | >5 g/kg                 | -        |
| 2-methoxy-1-methylethyl acetate | LD50 Oral                       | Rat     | 8532 mg/kg              | -        |
|                                 | LD50 Dermal                     | Rabbit  | 13 g/kg                 | -        |
| 1-methoxy-2-propanol            | LD50 Oral                       | Rat     | 6600 mg/kg              | -        |
|                                 | LD50 Dermal                     | Rabbit  | 630 mg/kg               | -        |
| phenol                          | LD50 Dermal                     | Rat     | 669 mg/kg               | -        |
|                                 | LD50 Dermal                     | Rat     | 669 mg/kg               | -        |
|                                 | LD50 Oral                       | Rat     | 317 mg/kg               | -        |

**Conclusion/Summary** : Not available.

#### Acute toxicity estimates

| Route                | ATE value  |
|----------------------|------------|
| Inhalation (gases)   | 6523.7 ppm |
| Inhalation (vapours) | 27.79 mg/l |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure                | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| styrene                 | Eyes - Mild irritant     | Human   | -     | 50 parts per million    | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 100 milligrams          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams          | -           |
| butanone                | Skin - Moderate irritant | Rabbit  | -     | 100 Percent             | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 14 milligrams  | -           |
| xylene                  | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams           | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams   | -           |
|                         | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters  | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams | -           |
| ethanediol              | Skin - Moderate irritant | Rabbit  | -     | 100 Percent             | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 1 hours 100 milligrams  | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 6 hours 1440 milligrams | -           |

## SECTION 11: Toxicological information

|                                |                        |               |   |                 |   |
|--------------------------------|------------------------|---------------|---|-----------------|---|
| 1-methoxy-2-propanol<br>phenol | Skin - Mild irritant   | Rabbit        | - | 555 milligrams  | - |
|                                | Skin - Mild irritant   | Rabbit        | - | 500 milligrams  | - |
|                                | Eyes - Mild irritant   | Rabbit        | - | 0.5 minutes     | - |
|                                | Eyes - Severe irritant | Rabbit        | - | 5 milligrams    | - |
|                                | Skin - Severe irritant | Rabbit<br>Pig | - | 5 milligrams    | - |
|                                | Skin - Mild irritant   | Rabbit        | - | 0.5 minutes     | - |
|                                | Skin - Severe irritant | Rabbit        | - | 400 microliters | - |
|                                |                        |               |   | 100 milligrams  | - |
|                                |                        |               |   | 535 milligrams  | - |

**Conclusion/Summary** : Not available.

### Sensitisation

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| styrene                 | Category 3 | Not applicable.   | Respiratory tract irritation |
| butanone                | Category 3 | Not applicable.   | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs  |
|-------------------------|------------|-------------------|----------------|
| styrene                 | Category 1 | Not determined    | hearing organs |

### Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| styrene                 | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Harmful if inhaled. May cause respiratory irritation.

**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

## SECTION 11: Toxicological information

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** :  Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

| Product/ingredient name                     | Result   | Species    | Dose                | Exposure     |
|---|--|------------|---------------------|--------------|
| <input checked="" type="checkbox"/> styrene | Chronic NOAEL Dermal<br>Chronic NOAEL Inhalation<br>Gas. | Rat<br>Rat | 615 mg/kg<br>20 ppm | -<br>8 hours |

- Conclusion/Summary** : Not available.
- General** :  Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** :  Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Other information** : Not available.



## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name         | Result                               | Species                                    | Exposure |
|---------------------------------|--------------------------------------|--|----------|
| styrene                         | Acute EC50 1400 µg/l Fresh water     | Algae - Pseudokirchneriella subcapitata    | 72 hours |
|                                 | Acute EC50 33 mg/l Fresh water       | Algae - Pseudokirchneriella subcapitata    | 96 hours |
|                                 | Acute EC50 4700 µg/l Fresh water     | Daphnia - Daphnia magna                    | 48 hours |
|                                 | Acute LC50 52 mg/l Marine water      | Crustaceans - Artemia salina               | 48 hours |
|                                 | Acute LC50 4020 µg/l Fresh water     | Fish - Pimephales promelas                 | 96 hours |
| butanone                        | Chronic NOEC 1.01 mg/l               | Daphnia                                    | 21 days  |
|                                 | Acute EC50 >500000 µg/l Marine water | Algae - Skeletonema costatum               | 96 hours |
| titanium dioxide                | Acute EC50 5091000 µg/l Fresh water  | Daphnia - Daphnia magna - Larvae           | 48 hours |
|                                 | Acute LC50 1690 mg/l                 | Fish                                       | 96 hours |
|                                 | Acute EC50 27.8 mg/l Fresh water     | Daphnia - Daphnia magna                    | 48 hours |
| xylene                          | Acute LC50 15.9 mg/l Fresh water     | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
|                                 | Acute LC50 >1000 mg/l                | Fish - Pimephales promelas                 | 96 hours |
| ethanediol                      | Acute LC50 8500 µg/l Marine water    | Crustaceans - Palaemonetes pugio           | 48 hours |
|                                 | Acute LC50 13400 µg/l Fresh water    | Fish - Pimephales promelas                 | 96 hours |
| ethylbenzene                    | Acute LC50 6900000 µg/l Fresh water  | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
|                                 | Acute LC50 41000000 µg/l Fresh water | Daphnia - Daphnia magna - Neonate          | 48 hours |
|                                 | Acute LC50 8050000 µg/l Fresh water  | Fish - Pimephales promelas                 | 96 hours |
| 2-methoxy-1-methylethyl acetate | Acute EC50 4.6 mg/l                  | Algae                                      | 72 hours |
|                                 | Acute EC50 2.96 to 4.4 mg/l          | Daphnia                                    | 48 hours |
| phenol                          | Acute LC50 4.2 mg/l                  | Fish                                       | 96 hours |
|                                 | Acute EC50 373 mg/l                  | Daphnia                                    | 48 hours |
| phenol                          | Acute LC50 >100 mg/l                 | Fish                                       | 96 hours |
|                                 | Chronic NOEC 16 µg/l Marine water    | Algae - Hormosira banksii - Gamete         | 72 hours |
|                                 | Chronic NOEC 1.5 mg/l Fresh water    | Daphnia - Daphnia magna                    | 21 days  |

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

| Product/ingredient name      | Aquatic half-life | Photolysis | Biodegradability |
|------------------------------|-------------------|------------|------------------|
| styrene                      | -                 | -          | Readily          |
| butanone                     | -                 | -          | Readily          |
| cobalt bis(2-ethylhexanoate) | -                 | -          | Not readily      |
| xylene                       | -                 | -          | Readily          |
| ethylbenzene                 | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name          | LogP <sub>ow</sub> | BCF         | Potential |
|----------------------------------|--------------------|-------------|-----------|
| styrene                          | 0.35               | 13.49       | low       |
| butanone                         | 0.3                | -           | low       |
| cobalt bis(2-ethylhexanoate)     | -                  | 15600       | high      |
| xylene                           | 3.12               | 8.1 to 25.9 | low       |
| ethanediol                       | -1.36              | -           | low       |
| ethylbenzene                     | 3.6                | -           | low       |
| (2-methoxymethylethoxy) propanol | 0.004              | -           | low       |
| 2-methoxy-1-methylethyl          | 1.2                | -           | low       |

Crystic Primecoat

## SECTION 12: Ecological information

|   |            |          |             |
|---|------------|----------|-------------|
| acetate<br>1-methoxy-2-propanol<br>phenol | <1<br>1.47 | -<br>647 | low<br>high |
|---|------------|----------|-------------|

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.




**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID  | IMDG   | IATA   |
|--|--|--|--|
| <b>14.1 UN number</b>                  | UN1866   | UN1866   | UN1866   |
| <b>14.2 UN proper shipping name</b>    | RESIN SOLUTION   | RESIN SOLUTION   | Resin solution   |
| <b>14.3 Transport hazard class(es)</b> | 3<br> | 3<br> | 3<br> |
| <b>14.4 Packing group</b>              | II   | II   | II   |

Crystic Primecoat

## SECTION 14: Transport information

|                                   |   |                                       |   |
|-----------------------------------|---|---------------------------------------|---|
| <b>14.5 Environmental hazards</b> | No.   | No.                                   | No.   |
| <b>Additional information</b>     | <b>Hazard identification number</b> 33<br><b>Limited quantity</b> 5 L<br><b>Special provisions</b> 640C<br><b>Tunnel code</b> (D/E) | <b>Emergency schedules</b> F-E, _S-E_ | <b>Quantity limitation</b><br>Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.<br><b>Special provisions</b> A3 |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

| Product/ingredient name       | Carcinogenic effects       | Mutagenic effects | Developmental effects         | Fertility effects          |
|-------------------------------|----------------------------|-------------------|-------------------------------|----------------------------|
| styrene                       | -                          | -                 | Repr. 2, H361d (Unborn child) | -                          |
| titanium dioxide              | Carc. 2, H351 (inhalation) | -                 | -                             | -                          |
| cobalt bis (2-ethylhexanoate) | -                          | -                 | -                             | Repr. 2, H361f (Fertility) |
| phenol                        | -                          | Muta. 2, H341     | -                             | -                          |

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

##### Category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

#### National regulations

Crystic Primecoat

## SECTION 15: Regulatory information

| Product/ingredient name      | List name                                  | Name on list     | Classification | Notes |
|------------------------------|--|------------------|----------------|-------|
| cobalt bis(2-ethylhexanoate) | UK Occupational Exposure Limits EH40 - WEL | cobalt compounds | Carc.          | -     |

### International regulations

Listed on inventory. : Not determined

### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification   | Justification   |
|--|---|
| ✔ Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Carc. 2, H351<br>Repr. 2, H361d (Unborn child)<br>STOT SE 3, H335<br>STOT RE 1, H372<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

### Full text of abbreviated H statements

: ✔ H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H301 Toxic if swallowed.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H311 Toxic in contact with skin.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H341 Suspected of causing genetic defects.  
 H351 Suspected of causing cancer if inhaled.  
 (inhalation)  
 H351 Suspected of causing cancer.  
 H361d Suspected of damaging the unborn child.  
 H361f Suspected of damaging fertility.

**SECTION 16: Other information**

H372 Causes damage to organs through prolonged or repeated exposure.  
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
 H373 May cause damage to organs through prolonged or repeated exposure if (oral) swallowed.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.

**Full text of classifications [CLP/GHS]**

Acute Tox. 3, H301 ACUTE TOXICITY (oral) - Category 3  
 Acute Tox. 3, H311 ACUTE TOXICITY (dermal) - Category 3  
 Acute Tox. 3, H331 ACUTE TOXICITY (inhalation) - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4  
 Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4  
 Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4  
 Aquatic Acute 1, H400 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1  
 Aquatic Chronic 3, H412 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  
 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1  
 Carc. 2, H351 (inhalation) CARCINOGENICITY (inhalation) - Category 2  
 Carc. 2, H351 CARCINOGENICITY - Category 2  
 EUH066 Repeated exposure may cause skin dryness or cracking.  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
 Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2  
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
 Muta. 2, H341 GERM CELL MUTAGENICITY - Category 2  
 Repr. 2, H361d REPRODUCTIVE TOXICITY (Unborn child) - Category 2  
 Repr. 2, H361f REPRODUCTIVE TOXICITY (Fertility) - Category 2  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITISATION - Category 1  
 Skin Sens. 1A, H317 SKIN SENSITISATION - Category 1A  
 STOT RE 1, H372 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1  
 STOT RE 2, H373 (inhalation) SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (inhalation) - Category 2  
 STOT RE 2, H373 (oral) SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (oral) - Category 2  
 STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2  
 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3  
 STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

**Date of printing** : 29/11/2017

**Date of issue/ Date of revision** : 29/11/2017

**Date of previous issue** : 15/03/2016

**Version** : 1.1

**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.