



Safety Data Sheet Duratec Sunshield 904-061 Clear Sealer

Updated April 2021

1. Identification of the Material and Supplier

Product Name: Duratec Sunshield 904-061 Clear
Product Code: DURATECSUNCL-1G
UN Number: 1263
DG Class: 3 – Flammable Liquid
Shipping Name: PAINT
Packaging Group: II
Hazchem Code: 3Y
Uses: Industrial and Professional use only
Company: H S Composites
Address: 63 Hunua Road, Papakura, Auckland 2110
Telephone: +64 (09) 295 2200
Email: sales@hscomposites.co.nz
Website: www.hscomposites.co.nz

2. Hazard Identification

Regulatory Information Surface Coatings and Colourants (Flammable) Group Standard 2017
HSNO Approval Number HSR002662
Dangerous Goods Class 3

Hazardous Classifications

Flammable Liquid	Category 2
Acute Toxicity if Inhaled	Category 4
Skin Corrosion/Irritant	Category 2
Serious Eye Damage/Irritation	Category 2
Respiratory Sensitization	Category 1
Reproductive Toxicity	Category 1
May cause Cancer by Inhalation	Category 1

Pictograms:



Signal Word: Danger

H226	Flammable liquid and vapor.
------	-----------------------------

HEALTH HAZARDS:

H226	Flammable Liquid and Vapour
H315	Causes Skin Irritation
H319	Causes eye irritation
H332	Harmful if inhaled
H334	May cause respiratory sensitization
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

ENVIRONMENT HAZARDS:

H401	Toxic to Aquatic life.
------	------------------------

PRECAUTIONARY STATEMENTS: Preventions

P102	Keep out of reach of Children
P103	Read Label/SDS before use
P201	Obtain instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flame/hot surfaces. No smoking.
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P260	Do not breathe vapours
P261	Do not breath dust/fumes/gas/mist/vapours/spray
P264	Wash hands and exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only in well-ventilated areas
P273	Avoid release into the environment
P280	Wear protective clothing, gloves and eye protection
P281	Use personal protective equipment as required

RESPONSE:

P101	If medical advice is needed, have product container or label at hand
P301 + P312	If swallowed call POISON CENTRE or DOCTOR if you feel unwell

Cobalt (II)2-ethylhexanoate	136-52-7	<=0.5%
------------------------------------	-----------------	------------------

4. First Aid

For advice, contact the National Poisons Centre (Phone New Zealand: 0800 764 766) or a doctor, show Doctor in attendance a copy of this SDS.

Inhalation: Move the person to fresh air immediately. Keep warm and at rest until recovered. Get medical advice if person feels unwell or is concerned. Begin artificial respiration if breathing has stopped and get immediate medical assistance.

Swallowed: If swallowed, DO NOT induce vomiting. Rinse mouth. Get medical advice. Begin artificial respiration if the victim is not breathing. Use mouth to nose rather than mouth to mouth. Obtain immediate medical attention

Skin Contact: If skin contact occurs, remove contaminated clothing and wash skin with soap and water. If skin irritation occurs, get medical advice. Launder contaminated clothing before re-use.

Eye Contact: Hold eyelids apart and flush the eye continuously with running water for 15 minutes. Remove contact lenses after 5 minutes if present, and easy to do. Continue flushing. Get immediate medical attention if irritation persists.

First Aid facilities: Provide eye baths and safety showers close to areas where splashing may occur.

Note to Doctor/Physician: Treat symptomatically. Show Dr this SDS notice.

5. Fire Fighting Measures

Flammable liquids and vapours: Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing fire fighters with this Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

Suitable extinguishing media: Carbon dioxide (CO₂), foam, water fog, sand or dry chemical.

DO NOT use Jetstream of water.

Hazards from combustion products: Smoke, fume, carbon dioxide and carbon monoxide and incomplete combustion products. May form explosive vapour/air mixture.

Precautions for fire fighters and special protective equipment: Full protective clothing and self-contained breathing apparatus.

Hazchem Code: 3Y

Flammable liquid and vapour. Vapour/Air mixture may ignite explosively. Flash back along vapour trail may occur. Run off into drains or sewer may create a fire or explosion hazard.

SPECIAL FIREFIGHTING PROCEDURES.

Wear full protective clothing and self-contained breathing apparatus in positive pressure mode, in case of fire the product may be violently or explosively reactive. Use water spray to disperse the vapours. Prevent product and vapours from entering drains/sewers/water courses.

6. Accidental Release Measures

Steps to be taken if the material is released or spilled.

Evacuate personnel to a safe area. Use Protective equipment as required. Ensure adequate ventilation in area. Make sure there is no risk to self or personnel.

Eliminate all sources of ignition (flames, hot surfaces, electrical, static or frictional sparks, no smoking). Then ventilate the area.

Contain the area of spillage and pump material into drums for use or disposal. Absorb remainder on sand or perlite and place the saturated absorbent into closed containers and label for disposal.

Prevent contamination of storm-water drains and waterways.

Contaminated absorbent to be disposed of in accordance with appropriate local or governmental regulations.

Correctly label all material containers to be disposed of.

7. Storage and Handling

Use Personal Protection. Avoid inhalation of vapour and contact with skin, eyes and clothing. Launder contaminated clothing before re-use, wash skin with soapy water. Wash hands thoroughly before eating.

This product is flammable, do not open near open flame, sources of heat or ignition, NO SMOKING.

Store in a locked and bunded area or approved flammable goods store away from direct heat (ideally below 25°C to prevent spoilage). Keep containers closed when not in use. Open drums slowly in case of internal pressure. Isolate from all potential sources of ignition including flames and electrical sparks.

Store separate from strong bases and acids.

Ground (earth) containers when using above flash point, -11.1°C.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Limits: Worksafe November 2020

Material	CAS #	TWA	STEL
Styrene	100-42-5	20ppm	40ppm
Methyl Ethyl Ketone	78-93-3	150ppm	300ppm
n-butyl acetate	123-86-4	150ppm	200ppm
Isobutyl acetate	110-19-0	150ppm	

General Use: This product is hazardous and should be used with a local exhaust ventilation to maintain vapour/dust concentration below WES level. If concentrations exceed exposure limit use organic vapour canister mask or approved air-line mask to maintain workshop limits.

Skin Protection: Wear overalls or other work clothing providing arm and leg cover. Use protective gloves (Latex or Nitrile). Use antistatic footwear.

Eye Protection: Safety goggles or splash mask.

Environmental Control: Prevent from entering into sewer, stormwater or waterways.



9. Physical / Chemical Properties

Physical Description & colour:	Clear liquid
Odour:	Aromatic odour
Boiling Point:	79.4°C
Flammable Liquid Flash Point:	-11.1°C
Flammable Limits:	No Data Available
Relative Density:	1.07
Vapour Density:	
Percent Volatiles:	No Data Available
Water Solubility:	Insoluble

10. Stability and Reactivity

- Stability:** Stable under normal storage and handling conditions.
- Conditions to avoid:** Exposure to sunlight, open flames and other sources of ignition, very low temperatures
- Materials to avoid:** Strong bases and acids.
Thermal decomposition may result in the release of toxic and/or irritating fumes carbon monoxide, carbon dioxide and various organic gases.
Polymerisation can take place and will form solid deposits.
Highly Flammable liquid and Vapour, may form explosive mixture.

11. Toxicological Information

When used under properly controlled conditions, within workplace exposure limits and with adequate ventilation and protective equipment, no adverse health effects are to be expected.

Acute effects of over exposure.

If Swallowed: Harmful by ingestion and may cause irritation to the mouth, throat, oesophagus with symptoms of nausea, vomiting and gastric disturbance.

Eye Contact: Moderate to serious irritation. Tearing, stinging, blurred vision and redness will occur if.

Skin Contact: This product can be absorbed through the skin causing harmful effects, irritation, redness, itching and swelling. Repeated exposure may result in dry skin, cracking or even dermatitis.

Inhalation of Vapour: Harmful if inhaled. May cause headaches, nausea, irritation to the nose, throat and respiratory system, possibility of serious health damage.

Chronic effects of overexposure:

Mild dermatitis may result from prolonged or repeated skin contact. Styrene can be absorbed through the skin. Seek medical advice

Excessive exposure to the liquid material or vapour may affect the central nervous system, the liver, kidneys and respiratory system.

Suspected of causing Cancer.

Suspected of causing damage to fertility and/or the unborn child.

May cause damage to organs through prolonged exposure.

12. Ecological Data

Prevent the product from entering storm-water drains, sewers or waterways.

Toxic to Aquatic life and harmful to the soil, may contaminate ground water if reached.

Will readily biodegrade over time by evaporation.

H401	Toxic to Aquatic life.
------	------------------------

13. Disposal Considerations

P501 Dispose of product and packaging in accordance with local regulations or through an approved waste disposal plant.

Empty containers may contain flammable residues/vapours, keep away from sources of ignition.

Dangerous Goods Classification 3

Packing Group II

Hazchem Code 3Y

14. Transport Information

UN Number: UN1263

Proper Shipping Name: PAINT

Hazchem Code: 3Y

Dangerous Goods Class: 3

Packing Group: II

Tunnel Restriction: D/E

Marine Pollutant: Yes

Special Precautions for users:

EMS Number F-E, S-D

IERG Code 128

DO NOT LOAD WITH – Explosives, toxic gases, spontaneously combustible substances, oxidisers or organic peroxides.

15. Regulatory Information

EPA New Zealand HSNO approval code HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2017

SDS To be available within 10 minutes when required.

16. Other Information

This SDS contains only safety-related information. For other data see product information literature.

Group Standard	October 2020
LEL	Lower explosive limit
UEL	Upper explosive limit
TWA	Time weighted average over 8 hr working day
STEL	Short term expose limit
Cas #	Unique registered number for chemicals
ppm	parts per million
UN number	Individual number assigned to hazardous materials
EMS	Emergency response for shipping
ERG	Emergency code for first responders
Other References	Manufacturers SDS's

Review: March 2021

Reason: Updates and pictograms

Disclaimer: The information given in this safety data sheet is given in good faith and is believed to be valid and accurate at the time of publication. However, no responsibility is accepted for accident or injury which may occur from omissions or from information contained in the data sheet.

JB SDS's 04/21