

# Chopped Strand Mat CSM

## Technical Datasheet



**Product:** Chopped Strand Mat CSM

**Product Code:** CSM-450-E

**Size:** 30kg roll 1040mm wide roll. One side with feather edge

**Uses:** Hand lay-up application in a wide range of fibreglass products.  
Boats, automotive parts, panels etc

**Features:** High strength Good mat integrity  
Excellent flexibility Good wetting-out  
High dry and wet tensile strength

### Technical Characteristics

Product Code	Area weight g/m2 ISO3374	Breakage Strength N ISO3342	Binder content % ISO1887	Moisture % ISO3344	Binder Type	Binder CAS number
CSM-450-E	450±45	≥120	3.0-5.0	≤0.15	Emulsion Bound	9003-20-7

### Packaging

Chopped strand mat is wound onto a 76mm diameter paper core, wrapped in plastic film and packed in a carton.

**HS Composites Ltd 63 Hunua Road, Papakura, Auckland 2110**  
**+64 (09) 295 2200 sales@hscomposites.co.nz www.hscomposites.co.nz**

Store in a dry, cool and rain-proof area



*Disclaimer: The information given in this data sheet is given in good faith and is believed to be valid and accurate at the time of publication. However, no responsibility is accepted for accident or injury which may occur from omissions or from information contained in the data sheet.*